# Ducted
# Fume Hood

LED Display

Waterproof Socket

Water&Gas Remote Control

**Double Layer**

1.2mm sheet metal surface, melamine board inward.

# ADVANTAGE

1. UV lamp for sterilization.
2. resistant to weak acid and alkali.
3. Adjustable air speed: 9 levels.
4. Motorized front window, height adjustable.
5. Microprocessor control system, LED display.
6. With memory function in case of power-failure.

# TECHNICAL PARAMETERS

| Model | | FH1000(A) | FH1200(A) |
|---|---|---|---|
| External Size (W*D*H) | | | 1240*800*2200mm |
| Internal Size (W*D*H) | | | 1020*670*730mm |
| Work Surface Height | | 850mm | |
| Max Opening | | 520mm | |
| Air Velocity | | 0.3~0.8m/s | |
| Noise | | ≤60dB | |
| Exhaust Duct | | PVC, Standard length: 4 meters. | |
| | | Φ300mm | |
| LED Lamp | | | 12W*1 |
| UV Lamp | | Emission of 253.7 nanometers for most efficient decontamination | |
| Blower | | Built-in centrifugal blower; Speed adjustable | |
| Front Window | | 5mm toughened glass; Motorized; Height adjustable | |
| Power Supply | | AC220V±10%, 50/60Hz; 110V±10%, 60Hz | |
| Consumption | | | 400W |
| Material | Exterior | Cold-rolled steel with anti-bacteria powder coating. | |
| | Interior | High grade melamine board with good acid and alkali resistance function | |
| | Work Table | Chemical resistant phenolic resin | |
| Standard Accessories | | UV lamp*2, LED lamp, Water tap, Gas tap, Water sink, Base cabinet | |
| | | Total load of 2 waterproof sockets: 500W | |
| | | 4 meter PVC exhaust duct, pipe strap*2 | |
| Optional Accessory | | Active carbon filter | |
| Gross Weight | | | 317kg |
| Package | Main Body | | 1390*990*1690 mm |
| | Base Cabinet | | 1390*990*980mm |

بغداد - شارع السعدون
مقابل تمثال السعدون
info@almubdaa.com
مكتب المبدع العلمي